

Manufacturer		NEOlift
Model		NOP10
Power Type		Battery
Operation Type		Stand on
Rated Capacity	kg	1000
Load Center	mm	500
Front Overhand	mm	160
Wheelbase	mm	1410
Service Weight(incl.battery)	kg	2830
Weight distribution when loaded, drive side/load side	kg	1130/2700
Weight distribution when unloaded, drive side/load side	kg	1610/1220
Wheel Types		PU
Load Wheel	mm	φ150×90
Drive wheel	mm	φ254×100
Number of wheels,,front/rear(x=drive wheel)		4/1X
Wheel tread,load side	mm	1008
Mast closed height	mm	2815
Lift height	mm	5760
Max lift height of fork	mm	6530
Mast extended height	mm	7955
Overhead guard height	mm	2250
Platform min.ground clearance	mm	240
Auxiliary lift height	mm	700
Platform max.ground clearance	mm	6000
Picking height (h12+1600mm)	mm	7600
Fork face min.ground clearance	mm	70
Overall length	mm	2835
Length to forkface	mm	1765
Overall width	mm	1150
Fork size	l/e/s(mm)	1070/100/40
Fork outside width	mm	700
Mast ground clearance	mm	50
Body ground clearance	mm	50
Aisle width for pallet 1000*1200	Ast(mm)	3130
Aisle width for pallet 800*1200	Ast(mm)	3245
Turning radius	Wa(mm)	1625
Driving speed(load/unload)	km/h	6/6.3
Lifting speed(load/unload)	mm/s	115/140
Lowering speed(load/unload)	mm/s	135/140
Brake type		Electromagnetic type
Driving motor(S2-60min)	kw	2.5
Lifting motor(S3-15%)	kw	3
Battery voltage/capacity	V/Ah	24/400
Battery weight	kg	350
Driving motor type		AC
Driver ear noise (EN12053)	dB(A)	70
Steering system		EPS